

Product Code: MD028PW

Luckinslive 389103385

Description: 10AX Intermediate Switch Module



General Information

Dimensions (mm)	25 (W) x 53 (H) x 20 (D)			
Colour	Polar White			
Materials	Rocker Switch: Urea		Rear Housing: Nylon	
	Terminals: Brass		Terminal Screws: Steel & Yellow Passivated	
	Contacts: Silver "on-lay" Copper / Brass		Internal Busbars: Formed Pressed Brass	
Anti Microbial Certified	Yes			
Operating Voltage (AC)	250	Frequency (Hz)	50	
Inductive Load Rating (AX)	10			
Load Rating Comments	Suitable for Fluorescent or Inductive Loads			
Termination Type	Screw			
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm)	0.5	
Terminal Capacity - Solid (mm²)	4 x 1.5 or 2 x 2.5			
Modular Rocker Switches	Yes			
Intermediate Switch	Yes			
Minimum Back Box Depth (mm)	16 (25 Flat Plate)			
Operational Temperature (°C)	-5 to +40			
Warranty (Years)	20			

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches the Definity, Mode, Polar & Part M ranges

